

## CLAIMS

- 1 1. A computer assisted method of auditing a superset of training data, the  
2 superset comprising examples of documents having one or more category  
3 assignments, the method including:
- 4 partitioning the superset into at least two disjoint sets, including a test set and a  
5 training set, wherein the test set includes one or more test documents and the  
6 training set includes examples of documents belonging belong to at least two  
7 categories;
- 8 categorizing the test documents using the training set;
- 9 calculating a metric of confidence based on results of the categorizing step and  
10 the category assignments for the test documents; and
- 11 reporting the test documents and category assignments that are suspicious and  
12 that appear to be missing, based on the metric of confidence.
- 1 2. The method of claim 1, further including repeating the partitioning,  
2 categorizing and calculating steps until at least one-half of the documents in the  
3 superset have been assigned to the test set.
- 1 3. The method of claim 2, wherein the test set created in the partition step has a  
2 single test document.
- 1 4. The method of claim 2, wherein the test set created in the partition step has a  
2 plurality of test documents.
- 1 5. The method of claim 1, further including repeating the partitioning,  
2 categorizing and calculating steps until substantially all of the documents in the  
3 superset have been assigned to the test set.
- 1 6. The method of claim 1, wherein the partitioning, categorizing and calculating  
2 steps are carried out substantially without user intervention.
- 1 7. The method of claim 5, wherein the partitioning, categorizing and calculating  
2 steps are carried out substantially without user intervention.
- 1 8. The method of claim 1, wherein the partitioning, categorizing, calculating and  
2 reporting steps are carried out substantially without user intervention.

1 9. The method of claim 5, wherein the partitioning, categorizing, calculating and  
2 reporting steps are carried out substantially without user intervention.

1 10. The method of claim 1, wherein the categorizing step includes determining k  
2 nearest neighbors of the test documents and the calculating step is based on a k  
3 nearest neighbors categorization logic.

1 11. The method of claim 10, wherein the metric of confidence is an unweighted  
2 measure of distance between the test document and the examples of documents  
3 belonging to various categories.

1 12. The method of claim 11, where the unweighted measure includes application  
2 of a relationship  $\Omega_0(\mathbf{d}_t, T_m) = \sum_{\mathbf{d} \in \{K(\mathbf{d}_t) \cap T_m\}} s(\mathbf{d}_t, \mathbf{d})$ , wherein

3  $\Omega_0$  is a function of the test document represented by the a feature vector  $\mathbf{d}_t$  and of  
4 various categories  $T_m$ ; and

5  $s$  is a metric of distance between the test document feature vector  $\mathbf{d}_t$  and certain  
6 sample documents represented by feature vectors  $\mathbf{d}$ , the certain sample  
7 documents being among a set of k nearest neighbors of the test document having  
8 category assignments to the various categories  $T_m$ .

1 13. The method of claim 10, wherein the metric of confidence is a weighted  
2 measure of distance between the test document and the examples of documents  
3 belonging to various categories, the weighted measure taking into account the density  
4 of a neighborhood of the test document.

1 14. The method of claim 13 where the weighted measure includes application of

2 a relationship  $\Omega_1(\mathbf{d}_t, T_m) = \frac{\sum_{\mathbf{d}_1 \in \{K(\mathbf{d}_t) \cap T_m\}} s(\mathbf{d}_t, \mathbf{d}_1)}{\sum_{\mathbf{d}_2 \in K(\mathbf{d}_t)} s(\mathbf{d}_t, \mathbf{d}_2)}$ , wherein

3  $\Omega_1$  is a function of the test document represented by the a feature vector  $\mathbf{d}_t$  and of  
4 various categories  $T_m$ ; and

5  $s$  is a metric of distance between the test document feature vector  $\mathbf{d}_t$  and certain  
6 sample documents represented by feature vectors  $\mathbf{d}_1$  and  $\mathbf{d}_2$ , the certain sample  
7 documents  $\mathbf{d}_1$  being among a set of k nearest neighbors of the test document

8 having category assignments to the various categories  $T_m$  and the certain sample  
9 documents  $d_2$  being among a set of  $k$  nearest neighbors of the test document.

1 15. The method of claim 1, wherein the identifying step further includes filtering  
2 the test documents based on the metric of confidence.

1 16. The method of claim 15, wherein the filtering step further includes color  
2 coding the identified test documents based on the metric of confidence.

1 17. The method of claim 15, wherein the filtering step further includes selecting  
2 for display the identified test documents based on the metric of confidence.

1 18. The method of claim 1, wherein the user interface is a printed report.

1 19. The method of claim 1, wherein the user interface is a file conforming to  
2 XML syntax.

1 20. The method of claim 1, wherein the user interface is a sorted display  
2 identifying at least a portion of the test documents.

1 21. The method of claim 1, further including calculating a precision score for the  
2 identified test documents.

1 22. A computer assisted method of auditing a superset of training data, the  
2 superset comprising examples of documents having one or more category  
3 assignments, the method including:

4 determining  $k$  nearest neighbors of the documents in the superset;

5 categorizing the documents based on the  $k$  nearest neighbors into a plurality of  
6 categories;

7 calculating a metric of confidence based on results of the categorizing step and  
8 the category assignments for the documents; and

9 reporting the documents and category assignments that are suspicious and that  
10 appear to be missing, based on the metric of confidence.

1 23. The method of claim 22, wherein the metric of confidence is an unweighted  
2 measure of distance between the test document and the examples of documents  
3 belonging to various categories.

1 24. The method of claim 23, where the unweighted measure includes application  
2 of a relationship  $\Omega_0(\mathbf{d}_t, T_m) = \sum_{\mathbf{d} \in \{K(\mathbf{d}_t) \cap T_m\}} s(\mathbf{d}_t, \mathbf{d})$ , wherein

3  $\Omega_0$  is a function of the test document represented by the a feature vector  $\mathbf{d}_t$  and of  
4 various categories  $T_m$ ; and

5  $s$  is a metric of distance between the test document feature vector  $\mathbf{d}_t$  and certain  
6 sample documents represented by feature vectors  $\mathbf{d}$ , the certain sample  
7 documents being among a set of  $k$  nearest neighbors of the test document having  
8 category assignments to the various categories  $T_m$ .

1 25. The method of claim 22, wherein the metric of confidence is a weighted  
2 measure of distance between the test document and the examples of documents  
3 belonging to various categories, the weighted measure taking into account the density  
4 of a neighborhood of the test document.

1 26. The method of claim 25, wherein the weighted measure includes application

2 of a relationship  $\Omega_1(\mathbf{d}_t, T_m) = \frac{\sum_{\mathbf{d}_1 \in \{K(\mathbf{d}_t) \cap T_m\}} s(\mathbf{d}_t, \mathbf{d}_1)}{\sum_{\mathbf{d}_2 \in K(\mathbf{d}_t)} s(\mathbf{d}_t, \mathbf{d}_2)}$ , wherein

3  $\Omega_1$  is a function of the test document represented by the a feature vector  $\mathbf{d}_t$  and of  
4 various categories  $T_m$ ; and

5  $s$  is a metric of distance between the test document feature vector  $\mathbf{d}_t$  and certain  
6 sample documents represented by feature vectors  $\mathbf{d}_1$  and  $\mathbf{d}_2$ , the certain sample  
7 documents  $\mathbf{d}_1$  being among a set of  $k$  nearest neighbors of the test document  
8 having category assignments to the various categories  $T_m$  and the certain sample  
9 documents  $\mathbf{d}_2$  being among a set of  $k$  nearest neighbors of the test document.

1 27. The method of claim 22, wherein the determining, categorizing and  
2 calculating steps are carried out substantially without user intervention.

1 28. The method of claim 22, wherein the identifying step further includes  
2 filtering the documents based on the metric of confidence.

1 29. The method of claim 28, wherein the filtering step further includes color  
2 coding the identified documents based on the metric of confidence.

1 30. The method of claim 28, wherein the filtering step further includes selecting  
2 for display the identified documents based on the metric of confidence.

1 31. The method of claim 22, wherein the user interface is a printed report.

1 32. The method of claim 22, wherein the user interface is a file conforming to  
2 XML syntax.

1 33. The method of claim 22, wherein the user interface is a sorted display  
2 identifying at least a portion of the documents.

1 34. The method of claim 22, further including calculating a precision score for  
2 the identified documents.

10044731.102401